



xx l/ sec



100% PVC



-10°C - +60°C



10 - 50 m

Super flexible braided PVC hose

Features

Ultra lightweight and great flexibility and water resistant

Top quality PVC raw material 80 Shore A

Superior abrasion resistance and unkinkable

Optional high-flow fittings with / without ball bearing swivel function, with plastic spring guard and all with BSPP direct seal system

Customer benefits

Best ergonomics and handling with tools

Long lifetime and flexibility for cold areas

Outstanding tensibility & tear strength

Best airflow and perfect function for all connections, including direct fit to tools or couplings/plugs

Technical data

Tubing material:	PVC (100%)
Hardness:	Shore A 80 ± 2
Standard color:	Medium blue
Optional colors:	Red, Blue and others
Working pressure:	20 bar (at 23°C)
Burst pressure:	60 bar (at 23°C)
Temperature range:	-10°C ~ + 60°C

THERMOPLASTIC HIGH QUALITY PVC BRAIDED HOSES
 Versions and technical data

Hose ID (mm)	Hose OD (mm)	Total Length per Roll* (m)	Packaging	Total Weight per Roll (kg)	Part Number
6.5	10.0	50 / Special order	Foil wrapping		125.3502
10	15.0	50	Foil wrapping		125.6502
12.7	19.0	50 / Special order	Foil wrapping		125.7502

(* Sold in precut lengths as specified on the length column above)

THERMOPLASTIC PVC BRAIDED HOSE SETS
 Versions and technical data

FITTINGS w/ pressed on	Hose ID x OD (mm)	Work Length (m)	Connection	Part Number
	10 x 15	10	1/4" M	175.6100
		10	3/8" M	175.6101
		15	1/4" M	175.6200
		15	3/8" M	175.6201
		20	1/4" M	175.6300
		20	3/8" M	175.6301

THERMOPLASTIC BRAIDED HOSE SETS WITH HIGH-FLOW COUPLINGS
 Versions and technical data

FITTINGS w/ pressed on	Hose ID x OD (mm)	Work Length (m)	Connection	Part Number
	10 x 15	10	Euro-coupler	175.6104
		15	Euro-coupler	175.6204
		20	Euro-coupler	175.6304